

GASO DUPLEX, GASO TRIPLEX AND GASO QUINTUPLEX PLUNGER AND PISTON PUMPS BY WHEATLEY AND GASO PUMP


Gasos, 5325-M, Quintuplex, Plunger Pump

Pumps in this series

5325-M

Specs

| Spec | U.S. Standard |
|---------------------------|---------------|
| Type: | quintuplex |
| Minimum Plunger Diameter: | |
| Maximum Plunger Diameter: | |
| Stroke length: | 3/4" |
| Maximum Working Pressure: | PSI |
| Rod/Piston Load: | 5130lb |
| Gallons per Minute: | |
| Barrels per Day: | |
| Brake Horse Power: | 125.0 |



Pump Curves

Hover over Power Curves to reveal RPM and GPM



Performance Data Table

| Pump | Plunger Dia. In. | Plunger Area Sq. In. | English Units | | | 50 RPM | | 200 RPM | | 350 RPM | | 500 RPM | |
|--------|---------------------|-------------------------|---------------|-------------|-------------------|--------|-----|---------|-----|---------|-----|---------|-----|
| | | | BPD per RPM | GPM per RPM | Max Press. PSI | BPD | GPM | BPD | GPM | BPD | GPM | BPD | GPM |
| 5325-M | | | | | | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |

Features/Benefits

GASO PLUNGER PUMPS

Ratings published here in are intended to be used only for preliminary planning purposes, and as such carried no warranties whatsoever. All applications for gas opines must be approved in writing. THE INFORMATION CONTAINED HERE IS TRANSCRIBED FROM A GASO TECHNICAL MANUAL FROMM THE 1960 - 70 - 70 . IEQ INDUSTRIES OR THE CUSTODIANS OF THIS WEBSITE ARE NOT RESPONSIBLE FOR ITS CONTENT.

GASO pumps are engineered to deliver the book plus values which have distinguished GASO pumps for over 60 years and to provide longer life and lower maintenance costs. Important design features include:

Power End Specifications

Power Frame. High-strength gray iron alloy casting with heavy wall sections well written to ensure rigid construction.

Crankshaft. Mounted with centerline of shaft on centerline of cross heads. Crankshaft may extend from either side of the pump.

Crankshaft Bearings. Interchangeable heavy-duty roller bearings.

Connecting Rods. Connecting rods have renewable Babbitt lined steel backed shell bearings at the crank end and bronze bushings at crosshead end.

Crossheads. Cross head tends are hardened and ground steel.

Lubrication. All power and parts are lubricated by splash system from oil in the crankcase reservoir. Power frame has an oil return channel, from front of the cross heads back to the crankcase, to permit constant circulation of oil and to help keep oil cool.

Fluid End Specifications

FLUID END BODY. Alloys which are stocked are Molybdenum alloy iron for crude oil and freshwater service, and steel for pumping petroleum products in hazardous locations. Aluminum bronze alloys are used for salt water and other corrosive liquids. Special alloys such as Hastalloy C, Inconel or stainless steel can be furnished upon request.

PLUNGERS. Plunger materials are available in: file hard steel, colmonoy's surfaced steel, solid ceramic, and chrome plated steel.

PACKING. Standard packing is a set of non-crushable lid tight packing rings. Other packing can be furnished for special applications.

PILUNGER LUBRICATION. Furnished by use of grip oilers or regulated flow of oil from a force-feed's lubricator. Lubricator is mounted on the pump with separate oil lines to each plunger.

Disclaimer I

This website is intended as a reference tool only. It has been constructed from published data that is based on manufacturer's sales and engineering documents that are either current, historical and obsolete. Much of the machinery data contained herein has been re-rated through the years with different engineering criteria which may be in conflict with legacy data. Much of the content published here is calculated online with the use of dynamic data using formulas and extrapolations considered to be sound engineering formulas and are correct to the degree that the data used is accurate. We have done our best to be as precise as possible in this posting but do not represent any of the calculations or performance data to be entirely accurate. The data published here is intended to be general information rather than actual and to serve as a reference rather than a technical absolute. The user of such data should confirm such information independently.

Copyright and Disclaimers

WheatleyGas.com is your resource for Gaso pumps, Gaso pump parts and a supplier of ORIGINAL GASO PARTS and equipment, new used and remanufactured Wheatley, GASO and Wheatley/GASO plunger and piston pumps and pump parts and is not affiliated with Wheatley/GASO Inc. or its parent company, National Oilwell Varco, p Copyright ©2017, IntelIQ Holdings, LLC. All rights reserved, *Used under license from IntelIQ Holdings, LLC.