#### NEW, USED, AND REFURBISHED PUMPS AND PARTS

# WHEATLEYGASO.COM

GASO DUPLEX, GASO TRIPLEX AND GASO QUINTUPLEX PLUNGER AND PISTON PUMPS BY WHEATLEY AND GASO PUMP

IEQ Industries Ltd PO Box 230097 Grand Rapids, MI 49523 Phone: 800.544.9053 | 616.452.6882

# Wheatley, HP600-AL (543Q-7L), Quintuplex, Plunger Pump


# **Pumps in this series**

HP600-AL (543Q-7L) HP600-AM (543Q-7M) HP600-H (543Q-7H) HP600-XL (543Q-7XL)

- 543 horsepower 7 1/8" stroke horizontal quintuplex single acting plunger pump
- Available in two fluid end materials
- Pump speeds up to 280 RPMÃ, Ã,Â


# **Specs**

U.S. Standard Spec quintuplex Type: Minimum Plunger Diameter: 33/8" Maximum Plunger Diameter: 41/4" Stroke length: Maximum Working Pressure: 2,169 PSI Rod/Piston Load: 19400lb Gallons per Minute: 612.6 21003 Barrels per Day: Brake Horse Power: 543.0



## **Pump Curves**

#### **Hover over Power Curves to reveal RPM and GPM**



## **Performance Data Table**

| Pump                    | English Units       |                         |                |                |                   | 50 RPM |     | 150 RPM |     | 250 RPM |     | 280 RPM |     |
|-------------------------|---------------------|-------------------------|----------------|----------------|-------------------|--------|-----|---------|-----|---------|-----|---------|-----|
|                         | Plunger Dia.<br>In. | Plunger Area Sq.<br>In. | BPD per<br>RPM | GPM per<br>RPM | Max Press.<br>PSI | BPD    | GРM | BPD     | GPM | BPD     | GPM | BPD     | GPM |
| HP600-<br>AL<br>543Q-7L | 4.250               | 14.1863                 | 75.011         | 2.1878         | 1368              | 3751   | 109 | 11252   | 328 | 18753   | 547 | 21003   | 613 |
|                         | 4.125               | 13.3640                 | 70.663         | 2.0610         | 1452              | 3533   | 103 | 10599   | 309 | 17666   | 515 | 19786   | 577 |
|                         | 4.000               | 12.5664                 | 66.446         | 1.9380         | 1544              | 3322   | 97  | 9967    | 291 | 16611   | 484 | 18605   | 543 |
|                         | 3.875               | 11.7932                 | 62.358         | 1.8188         | 1645              | 3118   | 91  | 9354    | 273 | 15589   | 455 | 17460   | 509 |
|                         | 3.750               | 11.0447                 | 58.399         | 1.7033         | 1757              | 2920   | 85  | 8760    | 255 | 14600   | 426 | 16352   | 477 |
|                         | 3.625               | 10.3206                 | 54.571         | 1.5917         | 1880              | 2729   | 80  | 8186    | 239 | 13643   | 398 | 15280   | 446 |
|                         | 3.500               | 9.6211                  | 50.872         | 1.4838         | 2016              | 2544   | 74  | 7631    | 223 | 12718   | 371 | 14244   | 415 |
|                         | 3.375               | 8.9462                  | 47.304         | 1.3797         | 2169              | 2365   | 69  | 7096    | 207 | 11826   | 345 | 13245   | 386 |

## Features/Benefits

- Cast iron power frame
- Ductile Iron crankshaft
- Heavy-duty, tapered roller crankshaft bearings
- Precision type, aluminum alloy crankpin bearings
- Ductile iron connecting rods
- Roller Type Center Main Bearings
- · Alloy steel crosshead pins
- Bronze bearing crosshead pin bushings
- Cast iron crossheads with upper/lower oil grooves
- Stainless steel extension rods
- Internal pressure lubrication
- Rated rod load is 19400 lbs.
- Bolted Type Valve Covers
- Removable Stuffing Boxes & Glands
- Plungers Solid Ceramic, or Tungsten coatedÃ, Ã,Â

#### Disclaimer I

This website is intended as a reference tool only. It has been constructed from published data that is based on manufacturer's sales and engineering documents that are either current, historical and obsolete. Much of the machinery data contained herein has been re-rated through the years with different engineering criteria which maybe in conflict with legacy data. Much of the content published here is calculated online with the use of dynamic data using formulas and extrapolations considered to be sound engineering formulas and are correct to the degree that the data used is accurate. We have done our best to be as precise as as possible in this posting but do not represent any of the calculations or performance data to be entirely accurate. The data published here is intended to be general information rather than actual and to serve as a reference rather than a technical absolute. The user of such data should confirm such information independently.

#### Copyright and Disclaimers

Wheatley/GASO parts and equipment, new used and remanufactured Wheatley, GASO and Wheatley/GASO pumps, Gaso pump parts and a supplier of ORIGINAL GASO PARTS and equipment, new used and remanufactured Wheatley, GASO and Wheatley/GASO plunger and piston pumps and pump parts and is not affiliated with Wheatley/GASO Inc. or its parent company, National Oilwell Varco, Copyright A©2024 IEQ Industries, a Gallagher Fluid Handling Company. All rights reserved, \*Used under license from IntelleQ Holdings, LLC.